

**BAXTA XERO ADADVANCED
SUPER COVER MATT**

RESOURCE CODE 117850
NOVEMBER 2019
PAGE 1 OF 4



Description & Uses

Baxta Xero Advanced Super Cover Matt is a high performance, ultra premium paint, delivering new levels of protection and durability. Its Total Cover technology offers exceptional covering power, advanced washability and stain resistance, with a low VOC formula beneficial for indoor air quality. Whatever your needs, Baxta Xero Advanced Super Cover Matt Advanced is the confident choice.

Features & Benefits

- | | |
|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • 2 Coat Coverage* • Easy clean • Stain resistant | <ul style="list-style-type: none"> • Smooth & uniform finish • Low VOC |
|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|

*When applied at nominated spreading rate with correct application technique.

Colours

SuperWhite base is tintable only with HydroChroma® water-based colourants to Baxta colours or other competitor colours.

Matt (Gloss level <5 at 60 degrees).

Environmental Data & Certifications



Approved to Australia Paint Approval Scheme Specification APAS 0260/4.



Verified to the Environmental Choice New Zealand (ECNZ) Specification EC-07-18.

**BAXTA XERO ADAVANCED
SUPER COVER MATT**

RESOURCE CODE 117850
NOVEMBER 2019
PAGE 2 OF 4

Properties & Performance Guide

Dry & Recoat Times	Surface Dry - 30 minutes Recoat - 2 hours Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 14 M ² /L depending on the surface texture, porosity and method of application.
Film Thickness	Wet Film Thickness (WFT) - 63 microns minimum Dry Film Thickness (DFT) - 26 microns minimum
Thinning	If required, thin with up to 5% water.
Clean Up	Clean up with cold water away from drains. Protect Our Environment: Do not pour leftover paint down the drain. To dispose of unwanted paint see paintback.com.au . Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle containers via recycling programs. Check with your local council first.
VOC (Volatile Organic Compounds)	VOC < 16g/Litre.

Recommended Substrate Conditions & Preparation

Surfaces are to be suitably prepared in accordance with proper trade practices. Ensure the surface is clean, dry and free from dust, dirt and grease. Remove loose, peeling or flaking material. Sand the surface smooth and remove all dust. Sand enamel painted surfaces to remove gloss. Fill holes and cracks with a suitable filler and sand lightly to an even finish.
All new cement surfaces need to be fully cured (typically 4–6 weeks) prior to painting. Ensure surfaces are free of bond breakers, formwork release agents and curing compounds.
If mould is present, clean surface with household bleach then rinse well with clean water.
Test soundness of previously painted surfaces by cutting a small X in the paint with a sharp blade. Stick a piece of tape firmly over the X and pull off. If the paint pulls away, the surface is unsound. Repeat at random in a number of areas. Unsound surfaces should be stripped for best results.

Application Guide

Stir well before and during use with a broad paddle reaching to the bottom of the can and lifting until contents are completely mixed.

Apply two full, even coats by brush, roller or spray.
Use a quality synthetic brush or synthetic roller.
Use a medium nap (12mm pile) synthetic roller on smooth and semi-smooth surfaces.
Use a longer nap (20mm pile) synthetic roller on rough surfaces, e.g. Besser Block.
Ensure that brushes and rollers are dry or only slightly damp with water before use.
Use a 13 or 15 thou Tip for airless spray.
Do not apply when temperature is below 10°C or above 35°C or when humidity is very high.

Surface Type

Preparatory Coats

Previously painted surfaces water-based.

No undercoat required on sound surfaces. Apply one coat of Baxta Acrylic Sealer Undercoat Low VOC where required to create an even base over patched or damaged surfaces, or to maximise opacity of topcoat.

**BAXTA XERO ADAVANCED
SUPER COVER MATT**

RESOURCE CODE 117850
NOVEMBER 2019
PAGE 3 OF 4

Surface Type...Continued	Preparatory Coats....Continued
Previously painted surfaces oil-based.	Apply one coat of Baxta Sealer Undercoat Low VOC.
Bare timber and MDF.	Apply one coat of Baxta Sealer Undercoat Low VOC. On tannin rich timber apply one coat of Baxta Timber Primer.
Bare cement render, brick, fibre cement and masonry.	Apply one coat of Baxta Sealer Undercoat Low VOC.
Bare paper-faced plasterboard.	Apply one coat of Baxta Sealer Undercoat Low VOC.

Additional Data

Available in 4, 10 & 15 litres.
Tinted paint is non-refundable, so choose your colours carefully.
If using more than one can for the final coat, check that the colour is correct in all cans and mix the paint together to ensure colour consistency before starting.
Avoid exposure to steam and condensation for 48 hours after application of final coat.
Leave 7 days after application of final coat before washing. Wash using a sponge or soft cloth with warm water and mild detergent. Avoid harsh scrubbing and strong household cleaners.
Containers must be secured and stored upright during transit.
Containers must not be exposed to excessive heat or cold.
Store in a secure, cool and well ventilated place. Keep container tightly closed.
The use of proprietary additives other than those manufactured by Baxta is not recommended.
Do not use for any other purpose other than as specified in our literature.

Safety Data

First Aid Instructions	For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.
Safety Directions	Keep out of reach of children. Avoid contact with skin and eyes. Ensure adequate ventilation during use. Avoid prolonged breathing of vapour. Wash hands thoroughly after use.
Further Information	For the latest information refer to the Safety Data Sheet available on our website. www.baxta.com.au or call 1300 852 240

BAXTA XERO ADAVANCED SUPER COVER MATT

RESOURCE CODE 117850

NOVEMBER 2019

PAGE 4 OF 4

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Baxta; (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the technical data sheet was prepared using information gathered during product development. While Baxta endeavours to update this information and maintain the accuracy of its contents, Baxta cannot guarantee that the information is wholly comprehensive.

3. Baxta recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Baxta Office.

4. To the full extent permitted by law, Baxta's liability for breach of a condition or warranty implied into the contract for sale between Baxta and you by law is limited at Baxta's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

Ph: 1300 852 240