

## TEXTURE COARSE SAND FINISH

RESOURCE CODE 210031  
FEBRUARY 2022  
PAGE 1 OF 3



### Description & Uses

Baxta Texture Sahara Fine White is an extremely versatile, subtle texture coating designed to give a convenient and economical means for simulating a sandy or 'bagged' finish. Baxta Texture Sahara Fine White may be applied by roller, brush or lambswool mitt in one or two coats. Baxta Texture Sahara Fine White may be left matt or overcoated for enhanced durability with Baxta Maxicap Elastomeric Paint Matt or Baxta Maxicap Shield Paint Low Sheen. Baxta Texture Sahara Fine White may be used to decorate, restore and protect commercial buildings, resorts, high-rise buildings, home sand offices.

### Features & Benefits

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• Simulate a sandy or 'bagged' finish</li> <li>• Interior and exterior use</li> </ul> | <ul style="list-style-type: none"> <li>• Applied by roller, brush or lambswool mitt.</li> </ul> |
|--|---|

### Colours & Gloss

White – Can be tinted to White Base colours.	Matt.
--	-------

### Properties & Performance Guide

Dry & Recoat Times	Surface Dry - 4 hours Recoat - 12 hours Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.	
Texture	<b>Roll On, Brush, Bagged</b> 10-12mm pile roller, block brush, lambswool mitt	<b>Ripple</b> Black Texture Roller
Coverage per Coat	0.4 L/M <sup>2</sup> (2.5 M <sup>2</sup> /L).	0.5 L/M <sup>2</sup> (2 M <sup>2</sup> /L).
Wet Film Thickness Dry Film Thickness	400 microns (approx). 195 microns (approx).	500 microns (approx). 240 microns (approx).
Thinning	Not required but if desired thin sparingly with water.	

### TEXTURE COARSE SAND FINISH

RESOURCE CODE 210031

FEBRUARY 2022

PAGE 2 OF 3

#### Properties & Performance Guide...Continued

Clean Up

Clean up with cold water away from drains.

**Protect Our Environment:** Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first.

#### Recommended Substrate Conditions & Preparation

**Work Area:** Care should be taken to keep product off windows and adjacent surfaces that are not to be coated, as product can be very difficult to remove once allowed to dry. Use drop sheets to cover surroundings surfaces. Ensure air movement and ventilation while painting. Keep doors and windows open.

**Substrate Condition:** Baxta Texture Sahara Fine White may be applied to a wide variety of suitably prepared surfaces including off-form concrete, cement rendered fair-faced flush-jointed concrete block and brickwork, CFC, tilt-up and pre-cast concrete, Autoclaved Aerated Concrete (AAC) and paper-faced plasterboard. The substrate must not be subjected to continual wetting or hydrostatic pressure. Surface preparation is the responsibility of the Builder, Renovator or Main Contractor and the Applicator. To achieve the indicated performance, application must be carried out according to Baxta's recommendation. For tilt-up and pre-cast concrete panels, Baxta Concrete Solvent Primer must be applied prior to application.

**Surface Prep:** Ensure the surface is clean and dry. All substrates must be free of dirt, grease, oil, mould, release agents, bondbreakers or any other contaminants that may interfere with adhesion. Fresh cementitious substrates should be left for a minimum 28 days before coating. There must be less than 15% moisture content in the surface at the time of coating to ensure optimum coating performance. The substrate must not be subjected to continual wetting or hydrostatic pressure. All substrates must be installed as per manufacturers' specifications prior to application.

#### Application Guide

Stir contents thoroughly with a power stirrer before use.

Applied in 1 or 2 coats to a correctly prepared and primed surface by 10-12mm pile roller (**Roll On** style), block brush (**Brush** style), lambswool mitt (**Bagged** style) or 1 coat by black texture roller (**Ripple** style).

**Note:** When Baxta Texture Sahara Fine White is overcoated with Baxta Maxicap Elastomeric Paint Matt or Baxta Maxicap Shield Paint Low Sheen only 1 coat of Baxta Texture Sahara Fine White is required. 2 coats of Baxta Texture Sahara Fine White are required if being left as a matt finish.

Baxta Texture Sahara Fine White can be overcoated with Baxta Maxicap Elastomeric Paint Matt or Baxta Maxicap Shield Paint Low Sheen for extra durability.

If Baxta Texture Sahara Fine White is used as the final coat in a 'matt' system specification, consistency of colour between different drums and/or batches cannot be guaranteed. Topcoating with Baxta Maxicap Elastomeric Paint Matt or Baxta Maxicap Shield Paint Low Sheen is recommended for consistency of colour, system longevity and ease of maintenance.

Freshly applied material must be protected from frosts and rain for a minimum of forty-eight (48) hours.

Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C or when humidity is very high. The temperature must not fall below 10°C during the drying process.

In exterior application avoid painting when dew or rain is likely.

### TEXTURE COARSE SAND FINISH

RESOURCE CODE 210031

FEBRUARY 2022

PAGE 3 OF 3

#### Additional Data

Available in 15 litre (25 Kg) containers.  
 Check colour is correct before applying. Manufacturer and distributor will accept no liability once product has been applied. For large projects box (or mix) pails to ensure colour consistency.  
 Avoid exposure to steam and condensation for 48 hours after application of final coat.  
 Leave 7 days after application of final coat before washing. Wash using a sponge or soft cloth with warm water and mild detergent. Avoid harsh scrubbing and strong household cleaners.  
 Not suitable for horizontal roofs, ponds or walk-on surfaces.  
 Containers must be secured and stored upright during transit.  
 Containers must not be exposed to excessive heat or cold.  
 Store in a secure, cool and well ventilated place. Keep container tightly closed.  
 Do not use for any other purpose other than as specified.

#### Manufacturers Comment

This product has been designed as part of a totally integrated coating system. Failing to follow application instructions or use with other manufacturer's product, could result in detrimental effects on product performance for which Baxta Industries Pty Ltd cannot be held responsible.

#### Safety Data

<p><b>First Aid Instructions</b></p>	<p>For advice, contact the Poisons Information Centre on 131 126 (Australia) or a doctor.                  If in eyes, wash out immediately with water. Remove contact lenses if present and easy to do so, continue rinsing.                  If skin contact occurs remove contaminated clothing and flush contaminated skin with water.                  If inhaled remove from contaminated area to fresh air.                  If swallowed, do not induce vomiting. Give a glass of water to drink.</p>
<p><b>Safety Directions</b></p>	<p>Keep out of reach of children.                  Avoid contact with skin and eyes.                  Ensure adequate ventilation during use.                  Avoid prolonged breathing of vapour.                  Wash hands thoroughly after use.</p>
<p><b>Further Information</b></p>	<p>Safety Data Sheet and Product Information can be found at <a href="http://www.baxta.com.au">www.baxta.com.au</a> or by calling 1300 85 55 40.</p>